

CONNECTORS

ALUMINUM WEDGE CONNECTOR WITH COPPER SPLINE TINNED

Used for electrical connections involving aluminum and copper wires and cables, in Aluminum - Aluminum and Aluminum - Copper combinations. Its installation is performed through the application tool. The spring effect connection prolongs the durability of the connection.



Features: spring-loaded connection (permanent tightening).

Material: aluminum body and wedge.

Application: electrical connections involving aluminum and copper wires and cables in Aluminum - Aluminum and Aluminum - Copper combinations.

AWG CONDUITORS	Stirrup (AWG)	CARTRIDGES	
4-2	2	RED	●
1/0 - 2/0	2	RED	●
3/0 - 4/0	2	BLUE	●
336,4	2	BLUE	●
8	2	RED	●
6	2	RED	●

AWG CONDUITORS	Stirrup (AWG)	CARTRIDGES	
8	2	RED	●
6	2	RED	●
4-2	2	RED	●
35 mm ²	2	RED	●
50 mm ²	2	RED	●
150 mm ²	2	BLUE	●
1/0 - 2/0	2	BLUE	●
3/0 - 4/0	2	BLUE	●
336,4	2	BLUE	●
150 mm ²	1/0	BLUE	●
336,4	1/0	YELLOW	●
336,4	4/0	YELLOW	●

Note: The Stirrup Connector is referenced by the main conductor plus stirrup.